

Product Highlights

- Operating temperature up to +150°C (+302°F)
- Clean aesthetic
- Expandable tubular sleeve
- Good abrasion resistance
- Excellent flexibility
- Self-extinguishing
- Fluid resistant

Typical Applications

- Wire harnesses
- Hoses and tubing



FlexFit® 2020 is an expandable sleeving specifically designed for full coverage of automotive wire harnesses, cables, tubings and hoses. Its specific structure uniquely combines materials to provide a high coverage and clean aesthetic allowing sleeve to disappear in sight all while providing critical functional protection.

FlexFit 2020 is constructed of a hybrid structure of specially prepared polyester monofilaments covered with polyester multifilaments. This unique construction ensures excellent appearance, protection against mechanical abrasion, resistance to common automotive fluids and self-extinguishing properties.



A customized specialized cutting method provides parts that have round opening for ease of installation.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – FlexFit® 2020

Property	Test Method	Result
Temperature Rating	240 hours at +150°C (+125°C rating)	Pass +150°C (+302°F)
Low Temperature Flexibility	SAE J2192	Pass -70°C (-94°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	SAE J2192	Pass

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Construction and Typical Product Characteristics

Polyester (PET) monofilament and multifilament

Standard Sizes

Nominal Diameter (mm)	Recommended Application Range mm (in)	
	Min Ø	Max Ø
12	10	14

* Application based variables will influence the sleeve size required. Routing geometry and application type may present installation and fit challenges that should be considered. Max and Min values above are for guidance only. There may be multiple variations of this braid designed to facilitate installation and optimize fit. Proper sleeve sizing should be confirmed by the end user. Please consult your local sales representative for recommendations and support.

Availability

Standard sizes are listed here. Additional sizes could be available upon request.

Available in spools and custom cut lengths. Recommended cut lengths are in 5mm increments. Please see regional drawings for cut length tolerances.

Standard color is black. Additional colors may be available.

Please consult your local sales representative for regional packaging details and standards.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600

EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560

Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565

www.systemsprotection.com

BentleyHarris®
Protection Products

For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

FF2020-EMEA(EN-A4)A