

FlexFit® 2118



Product Highlights

- Operating temperature up to +150°C (+302°F)
- Slightly expandable tubular sleeve
- Excellent abrasion resistance
- Excellent flexibility
- Attractive appearance

Typical Applications

- Wire harnesses
- Hoses and Tubings



FlexFit® 2118 is a flexible, slightly expandable sleeve specifically designed for abrasion/ mechanical protection of wire harnesses, tubing and hoses. Braided with polyester multifilaments, it is lightweight, and rugged yet has a very attractive appearance. A high coverage ratio contributes to the product's aesthetic appeal and makes it suitable for visible applications.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data - FlexFit® 2118

Property	Test Method	Result
Temperature Rating	240 hours at +175°C (+150°C rating)	Pass +150°C (+302°F)
Low Temperature Flexibility	BH100-016A	Pass -70°C (-94°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	BH100-003B	Pass
Melt Temperature	ASTM D3418	245°C to 265°C (+473°F to +509°F)

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Construction and Typical Product Characteristics

Polyester (PET) multifilament

Availability

FlexFit 2118 is available in a range of sizes and cut to your specification. Standard color is black. Please contact your sales representative for availability.





BentleyHarris®