



## Product Highlights

- Operating temperature up to +260°C (+500°F)
- Excellent thermal protection
- Excellent splash protection
- Retards burn-through

## Typical Applications

- Fuel Lines
- Brake lines
- Power steering hose
- Heater hose

**FyreJacket® 1615** is a knitted fiberglass sleeve coated with silicone rubber that provides thermal protection up to +260°C (+500°F). The sleeve provides excellent protection for cables, hoses, and hydraulic lines. FyreJacket 1615 also has the capability to protect fuel and gas lines against short term hazards such as a flame blast. When burn-through is a threat, the specially designed sleeve construction retards the penetration of flame. This allows critical components to continue to function for a short amount of time.

In addition to protecting assemblies and components from high temperatures and flame, FyreJacket 1615 can be used to insulate lines and cables. This type of insulation protects external components from heat while often increasing the efficiency of the internal components.

The braided construction of FyreJacket 1615 allows excellent flexibility in temperatures as low as -60°C (-76°F). The silicone coating is highly resistant to a wide range of solvents and fluids.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

# Performance Data – FyreJacket® 1615

Property	Test Method	Result
Temperature Rating	240 hours at +285°C (+260°C rating)	Pass +260°C (+500°F)
Low Temperature Flexibility	BH100-016A	Pass -60°C (-76°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	BH100-003B	Pass

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

## Construction and Typical Product Characteristics

<b>Outer Layer</b>	Silicone rubber coating
<b>Inner Layer</b>	Fiberglass multifilament

## Availability

FyreJacket 1615 is available in a range of sizes and cut to your specification. Standard colors are black, orange or silver. Please contact your sales representative for availability.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600

EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560

Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565

[www.systemsprotection.com](http://www.systemsprotection.com)

**BentleyHarris®**  
Protection Products

For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

FJ1615-GL(EN-A4)A