



Product Highlights

- Operating temperature from -55°C to +1100°C (-67°F to +2012°F) (depends on type)
- A-A-52083* Finish D (TG Series)
- A-A-52084 Finish C (HT-25-C)
- NSA8420 (NT-40)
- Anti-fray
- Good knot slip resistance

Lacing Tapes are flat braided textiles used for spot ties, cable-lacing and harnessing applications. The lacing tapes are offered in Teflon®-coated fiberglass (TG series), Nomex® (HT-25-C) and Nextel® (NT-40).

The TG series consists of Teflon-coated fiberglass, and conforms to Commercial Item Description A-A-52083 Finish D. TG lacing tapes also feature additional knot holding, anti-fray treatments as allowed by paragraph 6.5.

The HT series lacing tapes are braided from Nomex fiber and meet the requirements of Commercial Item Description A-A-52084 Finish C. Natural meta-aramid yarns with a green tracer are used along with a proprietary resin coating to improve knottability and reduce end fray.

NT-40 is a Nextel braided lacing tape with Teflon coating insuring anti-fray. NT-40 has outstanding heat and flame resistance up to +1100°C.

Teflon and Nomex are registered trademarks of E.I. DuPont de Nemours.

Nextel is a registered trademark of 3M Corporation.

** The General Services Administration has authorized the use of this CID as a replacement for Type IV of MIL-T-43435B for all federal agencies.*



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – Lacing Tapes

Teflon Coated Fiberglass A-A-52083 Finish D (MIL-T-43435B Type IV* Finish D)

Commercial Part Number	Temperature Range	Width mm (in) +/- 10%	Thickness mm (in) +/- .008	Break Strength daN (lbs)	Packaging m (yd)
Lacing Tape TG-20	-55°C to +427°C (-67°F to +801°F)	1.52 (.060")	0.4 (.016")	22 (50)	457 (500)
Lacing Tape TG-30		2.16 (.085")	0.4 (.016")	33 (75)	457 (500)
Lacing Tape TG-40		2.80 (.110")	0.4 (.016")	44 (100)	228 (250)

TG = Natural color

Aramid Tape A-A-52084 Finish C

Commercial Part Number	Temperature Range	Width mm (in)	Thickness mm (in)	Break Strength daN (lbs)	Packaging m (yd)
Lacing Tape HT-25-C	-55°C to +260°C (-67°F to +500°F)	1.92+/-0.19 (0.0755+/-0.0075)	0.31+/- .076 (0.012+/-0.003)	15.5 (35)	457 (500)

HT-25-C = Natural with dark green tracer strand

Teflon Coated Nextel NSA8420

Commercial Part Number	Temperature Range	Width mm (in)		Thickness mm (in)		Maximum Mass g/m (lbs/ft)	Packaging m (yd)
		Min Ø	Max Ø	Min Ø	Max Ø		
Lacing Tape NT-40	-55°C to +1100°C (-67°F to +2012°F)	2.4 (0.094")	3.45 (0.136")	0.75 (0.030")	1.35 (0.053")	3.8 (0.003)	228 (250)

New: NT-40 is Nextel braided lacing tape with Teflon coating insuring anti-fray. NT-40 has outstanding heat and flame resistance up to +1100°C (+2012°F).

NT-40 = Natural color

Part Numbering System

Example	Product Name	Quantity
	Lacing Tape NT-40	228m

*The General Services Administration has authorized the use of Commercial Item Description A-A-52083 as a replacement for Type IV of MIL-T-43435B for all federal agencies.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.systemsprotection.com



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

LACETAPE-GL(EN-A4)E