



Product Highlights

- Operating temperature up to +150°C (+302°F)
- Light to moderate abrasion protection
- Low profile and easy to install cable bundling
- Self-wrapping design allows for break-outs
- Lightweight & flexible

Typical Applications

- Instrument panel harnesses
- Engine compartment harnesses
- Other body wiring harnesses
- Tube, hose, and cable assemblies

TwistWrap® 2403 is a self-wrapping sleeve designed to enable fast and easy wire harness bundling. Woven of both monofilament and multifilament polyester yarns the product is both flexible and lightweight. The polyester construction eliminates problems associated with trapped heat and humidity. The combination of materials also enables the product to provide a level of abrasion protection for the wire bundle.

TwistWrap 2403 maintains a circular profile when flexed and its unique design easily allows for breakouts and installation over completed assemblies.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – TwistWrap® 2403


Property	Test Method	Result
Temperature Rating	240 hours at +175°C (+150°C rating) ISO 6722	Pass +150°C (+302°F) No visible degradation nor loss of flexibility - Shrinkage < 10%
Low Temperature Flexibility	SAE J2192	Pass -70°C (-94°F)
Flammability	FMVSS 302 D45 1333	Pass Self extinguishing - Type B
Fluid Resistance	D47 1924	No visible degradation or alteration after being immersed during 24 hrs in the typical automotive fluids

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Construction and Typical Product Characteristics

Warp Yarn: Polyester (PET) multifilament

Fill Yarns: Polyester (PET) monofilament



End view of TwistWrap 2403 illustrating self-curling wrappable construction with nominal overlap.

Standard Sizes

Commercial Part Number	Nominal Diameter mm	Recommended Application Range mm	
		Min Ø	Max Ø
TwistWrap 2403 5-3	5	1	5
TwistWrap 2403 8-3	8	5	8
TwistWrap 2403 10-3	10	8	10
TwistWrap 2403 13-3	13	10	13
TwistWrap 2403 16-3	16	13	16
TwistWrap 2403 19-3	19	16	19
TwistWrap 2403 25-3	25	19	25
TwistWrap 2403 29-3	29	25	29
TwistWrap 2403 32-3	32	29	32
TwistWrap 2403 38-3	38	32	38

* Max diameter is defined as a nominal 90° sleeve overwrap. A variety of application-based variables will dictate the appropriate sleeve size for use on each harness. Proper sleeve sizing is at the discretion of the end user. A reduced overlap could be acceptable in certain applications allowing for a larger max diameter harness. Please consult your local sales representative for recommendations and guidance.

Availability

Standard sizes are listed here, Additional sizes could be available upon request.

Available in spools and custom cut lengths.
Recommended cut lengths are in 5mm increments.
Please see regional drawings for cut length tolerances.

Standard color is black.

Please consult your local sales representative for regional packaging details and standards. TwistTool is available as an installation aid for sizes 5, 8 and 13 mm.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.systemsprotection.com

