

Product Highlights


- Operating temperature up to +1093°C (+2000°F)
- Flexible: easy to install and route
- Crush resistant
- High strength-to-weight ratio
- Fluid resistant
- Corrosion resistant
- Abrasion protection
- Attractive appearance

Typical Applications

- Flexible exhaust pipes
- Flexible spouts on oil dispensers
- Hot-air duct for space heaters
- High velocity air conditioning systems
- Shielding / Conduit for electrical wiring
- Armoring for supply lines



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)



ClevaFlex® Air Handling Ducts are corrugated, stainless steel, flexible ducts with interlocked seams that are folded flat for airtightness, strength and flexibility.

Their proprietary, spiral-winding manufacturing process produces lightweight yet strong, flexible ducts that withstand temperatures in excess of +1093°C (+2000°F).

Mini-D has a double-ply construction, while Mini-E is single-ply. Type 304 stainless steel material is standard and offers moderate corrosion resistance.

Mini-D & Mini-E flexible ducts are ideally suited for handling hot fumes, corrosive exhausts, or high-velocity air streams.

Performance Data – Clevaflex® Mini-D & Mini-E Flexible Ducts

Construction and Typical Product Characteristics

| | |
|---------------------------------|---|
| Nominal Inside Diameters | Ranging from 22mm to 80mm Additional ID's can be developed based on customer requirements. |
| Lengths | Any length available up to a maximum continuous length of 100 feet. |
| Sleeve Construction | Mini- D: single-ply with 50% overlap Mini-E: single-ply |
| Materials | .004" Stainless Steel T304 (standard) |

Availability

Please contact our sales or engineering offices for product specifications and product offerings.



Clevaflex Mini-D and Mini-E flexible ducts withstand temperatures in excess of +1093°C (+2000°F).



United States: (1) 800 926 2472 • **México:** (52) 442 101 8100 • **Brazil:** (55) 19 3116 1600
EMEA: (33) 3 44 39 06 06 • **Japan:** (81) 45 330 0300 • **China:** (86) 21 6182 7560
Southeast Asia: (66) 35 276 400 • **Korea:** (82) 44 861 6368 • **India:** (91) 124 4784565
www.systemsprotection.com



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

CFFD-GL(EN-LTR)A