



Product Highlights

- Operating temperature from -60°C to +240°C (-76°F to +464°F)
- ASD EN 6049-003
- 1:2 expansion ratio
- Thin wall
- Lightweight
- Self-extinguishing
- Excellent abrasion protection
- Resistant to gamma and x-rays
- Water repellent

Expando® HTNS-L/HO is a thin wall braided sleeve manufactured from the meta-aramid Nomex®. Its highly expandable structure allows easy installation over long lengths even after the fitting of end connectors with a limited range of product sizes.

Expando HTNS-L/HO's flexible, expandable and non-flammable properties ensure excellent performance in the most diverse and aggressive environments. The product is designed for the protection of wire and cable bundles against flame, high temperatures, and mechanical abrasion.

The properties of Expando HTNS-L/HO ensure excellent resistance to gamma and x-rays.

Expando HTNS-L/HO has a water repellent treatment (HO) to reduce humidity absorption and to improve impermeability to fluids.

Expando HTNS-L/HO has various applications in the military, marine and aeronautical industries.

Expando products are tough, lightweight oversleeves used to protect cable assemblies, hoses and wire harnesses from chafing, cutting and abrading. The open-braid construction of Expando products enables each size to expand to fit several application shapes and diameters. This open-textile construction also makes them highly flexible and resistant to trapping water, heat and humidity.

Nomex is a registered trademark of E.I. DuPont de Nemours.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – Expando® HTNS-L/HO

| Property | Test Method | Result |
|------------------------------|---|--|
| Operating Temperature | | -60°C to +240°C (-76°F to +464°F) (continuous) Up to +310°C (+590°F) (short term) |
| Carbonization | Above +370°C (+698°F) | Does not melt |
| Abrasion Resistance | EN 6059 Part 403 | Pass |
| Flame resistance | FAR 25 AMDT.25-72 § 853(b) | Pass |
| Fluid resistance | EN 6059 Part 303 (24h with various temperatures) | Pass |
| Fuel: JP5 (NATO F44) | | Pass |
| Hydraulic fluids | | Pass |
| Skydrol 5 00 B4 & L D4 | | Pass |
| Mineral oil: MIL-L-7870A | | Pass |
| Synthetic oil: MIL-L 23699 | | Pass |
| Cleaning fluids: Forane | | Pass |
| 141B & MIL-L-87936 | | Pass |
| De-Icing fluid: MIL-A-8243 | | Pass |
| Humidity resistance | 1000 h at +150°C (+302°F) in air saturated with water vapor | Retains 70% of its original tensile strength |
| Water repellent | EN 6059 Part 305 | Pass |

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Product Specifications

Longitudinal shrinkage should be taken into account when utilizing expansion properties of the sleeve

| Commercial Part Number | Recommended Application Range mm (in) | | Max Weight g/m (lbs/ft) | Standard Packaging m (ft) |
|------------------------|--|--------------|----------------------------|------------------------------|
| | Min Ø | Max Ø | | |
| Expando HTNS-L/HO 2-X | 1 (1/32") | 2 (1/16") | 3.0 (0.002) | 100 (328') |
| Expando HTNS-L/HO 4-X | 2 (1/16") | 4 (3/16") | 4.0 (0.003) | 100 (328') |
| Expando HTNS-L/HO 6-X | 4 (3/16") | 8 (5/16") | 8.5 (0.006) | 100 (328') |
| Expando HTNS-L/HO 8-X | 6 (1/4") | 12 (7/16") | 11.5 (0.008) | 50 (164') |
| Expando HTNS-L/HO 10-X | 8 (5/16") | 16 (5/8") | 14.0 (0.009) | 50 (164') |
| Expando HTNS-L/HO 15-X | 10 (3/8") | 20 (3/4") | 17.5 (0.012) | 50 (164') |
| Expando HTNS-L/HO 20-X | 12 (7/16") | 24 (15/16") | 22.0 (0.015) | 50 (164') |
| Expando HTNS-L/HO 25-X | 15 (9/16") | 30 (1-3/16") | 32.5 (0.022) | 50 (164') |
| Expando HTNS-L/HO 30-X | 20 (3/4") | 40 (1-1/2") | 39.5 (0.027) | 50 (164') |

X = Color Code: 5 = green 9 = ivory 2 = red 0 = black 3 = orange

Part Numbering System

| Example | Description | Size | Color | Quantity |
|---------|-------------------|------|-----------|----------|
| | Expando HTNS-L/HO | 4 | 5 (green) | 100m |



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.systemsprotection.com



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

EXPHTNSLHO-GL(EN-LTR)C