

Product Highlights

- Operating temperature
-50°C to +150°C
(-58°F to +302°F)
- Expandable tubular sleeve
- Excellent noise suppression
- Abrasion resistant
- Extremely lightweight
- Highly expandable
- Self-extinguishing

Typical Applications

- Body wiring harnesses
- Instrument panel harnesses
- Dome light wiring harnesses



QuietSleeve® 3430 is a highly flexible, expandable sleeving used to suppress noise on wire harnesses. Its lightweight construction also provides additional protection against rubbing.

QuietSleeve 3430 is braided from a combination of monofilament polyester abrasion-resistant strands and multifilament, polyester, noise-suppression strands. When installed on wire harnesses, this construction provides a sound dampening and anti-rattle effect greatly reducing the noise generated by vehicle vibration.

QuietSleeve 3430 is easy to apply and one size fits many applications since it readily expands. In addition, the open weave construction prevents condensation.

The carefully calculated mix of strands provides a balance of key features including: flexibility, expandability, abrasion resistance, noise suppression and self-fitting recovery. These features optimize the handling properties of the sleeving and assure a longer service life for the final assembly.



Our manufacturing sites are
certified ISO 9001, IATF 16949,
or AS/EN 9100, ISO 14001
and ISO 45001 (Selected Sites)

Performance Data – QuietSleeve® 3430

Property	Test Method	Result
Temperature Rating	240 hours at +175°C (+150°C rating)	Pass +150°C (+302°F) with no visible degradation nor loss of flexibility Shrinkage ≤ 10%
Low Temperature Flexibility	BH100-016A	Pass -50°C (-58°F)
Flammability	FMVSS 302 D45 1333	Pass Self extinguishing Type B
Fluid Resistance	D47 1924	No visible degradation or alteration after being exposed to the following test cycles: <ul style="list-style-type: none"> Immersion for 15s at 23°C, followed by a drying period of <ul style="list-style-type: none"> – 24h at 150°C: motor oil, automatic transmission fluid, mineral hydraulic fluid. – 24h at 23°C: zinc chloride, brake fluid. Immersion for 48h at 70°C, followed by a drying period of 24h at 23°C: Urea of clean up Ad blue. Immersion for 24h <ul style="list-style-type: none"> – At 40°C, followed by a drying period of 4h at 23°C: for gazole, unloaded petrol 98, Std fuel C + 15% methanol, E85 bio ethanol. – At 70°C, followed by a drying period of 4h at 23°C, for windscreen washer. – At 118°C, by a drying period of 4h at 23°C, for engine coolant.
Noise Suppression	SAE J2192	Rubbing: > 20dB Rattling: > 44 dB

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Construction and Typical Product Characteristics

Resilient Support Yarn: Polyester (PET) monofilament

Noise Suppression Yarn: Polyester (PET) multifilament

Availability

QuietSleeve 3430 is available in a range of sizes and cut to your specification. Standard color is black with a red, temperature identifying, tracer strand. Please contact your sales representative for availability.

Standard Sizes

Commercial Part Number	Recommended Application Range mm		Max. Diameter Expansion mm
	Min Ø	Max Ø	
QuietSleeve 3430 3	1	4	7
QuietSleeve 3430 4	2	5	12
QuietSleeve 3430 6	2	6	16
QuietSleeve 3430 14	6	10	22
QuietSleeve 3430 18	10	14	30
QuietSleeve 3430 22	12	16	50



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.systemsprotection.com



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

QSL3430-NA(EN-LTR)A