


### Product Highlights

- Operating temperature from -65°C to +200°C (-85°F to +392°F)
- High Performance EMI Shielding
  - $R_o \text{ max} = 5 \text{ m}\Omega$
  - $L_t = 0.6 \text{ nH/m}$
- FAR Part 25.853
- Halogen-free
- Self-wrapping design
- EN45545-2
- NFPA 130
  - ASTM E-162
  - ASTM E-662
- BSS 7239
- SMP 800-C
- Fast and easy installation
- Stable construction
- Ideal for reworking components without disconnecting them
- Blue tracer line indicating the maximum operating diameter
- Cu/Ni metal (ASTM B-355)



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

## 95% Optical Coverage



**ROUNDIT® EMI FMJ (Full Metal Jacket)** is a wrap-around sleeving designed for high performance EMI shielding of wire and cable bundles. ROUNDIT EMI FMJ is manufactured from PPS monofilaments and nickel plated copper.

The self-wrapping feature of ROUNDIT EMI FMJ allows for quick and easy installation and removal of the product for assembly and maintenance.

The design offers innovative solutions to the protection of breakout areas and also provides ease of removal when inspection or maintenance of cables is necessary.

The stable construction guarantees the same level of EMI shielding regardless of the diameter on which it is installed within the recommended application range.

As an additional benefit, ROUNDIT EMI FMJ enables users to stock a limited range of sizes to cover a wide range of cable and wire diameters.


Thanks to its unique geometry and metal insertion, ROUNDIT EMI FMJ is easy to clamp with existing solutions.

ROUNDIT EMI FMJ has many applications in the aeronautical, space and military industries.



As an added benefit, the patented ROUNDIT® Tool will help improve installation time and is designed to install ROUNDIT® products on cable and wire configurations.

# Performance Data – ROUNDIT® EMI FMJ

Property	Test Method	Result
<b>PHYSICAL</b>		
Operating temperature range	Thermal endurance & shocks	-65°C to +200°C (-85°F to +392°F)
Rapid change of temperature	EN 2591-305	Pass
Flammability/smoke density/toxicity	FAR Part 25 § 853 & ABD 031 NF16101-16102 EN 45545-2	Conforms I3 F0 R22 HL3 R23 HL3
<b>MECHANICAL</b>		
Dynamic cut-through	EN 6059 Part 405	Pass
Bending	EN 6059 Part 402	Pass
Hard Vacuum Total Mass Loss (TML) Collected Volatile Condensable Material (CVCM) Water Vapor Recovery (WVR)	ASTM E-595	Meets industry standards 0.03% 0.01% 0.02%
<b>CHEMICAL</b>		
<b>Fluid Resistance</b> Jet Fuel: JP4 (NATO F44), Hydraulic Fluid: Skydrol 500 B4, Mineral Oil: MIL-L-7870A, Synthetic Oil: MIL-L-23699, Cleaning fluids: MIL-L87936, De-icing Fluid: MIL-A-8243	EN 6059-303	Pass
Salt spray resistance	EN 2591-307 – 96 hours	Pass
Mould Growth	EN 6059 Part 306	Pass
<b>EMI PERFORMANCE</b>		
Resistance Measurement  EN 3475-301 Ro max size 8 - 5.5 mΩ Ro max other sizes - 5 mΩ  Transfer Impedance  IEC 62153-4-3 Triaxial method on straight installation Lt = 0.6 nH		
Lightning	EN 2591-214 – Waveform 1 10KA	Pass

## Product Specifications

Commercial Part Number	Recommended App. Range mm (in)		Typical Weight g/m (lbs/ft)	Maximum Weight g/m (lbs/ft)	Maximum Backshell Diameter mm (in)	Standard Packaging m (ft)	Packaging for Space Applications m (ft)
	Min Ø	Max Ø					
ROUNDIT EMI FMJ 8-8	5 (3/16")	8 (5/16")	40 (0.027)	42 (0.028)	10 (3/8")	250 (820')	100 (328')
ROUNDIT EMI FMJ 13-8	8 (5/16")	13 (1/2")	60 (0.040)	63 (0.042)	16 (5/8")	175 (574')	50 (164')
ROUNDIT EMI FMJ 19-8	13 (1/2")	19 (3/4")	85 (0.057)	89 (0.060)	23 (7/8")	125 (410')	25 (82')
ROUNDIT EMI FMJ 25-8	19 (3/4")	25 (1")	107 (0.072)	111 (0.074)	31 (1-1/4")	75 (246')	25 (82')
ROUNDIT EMI FMJ 32-8	25 (1")	32 (1-1/4")	144 (0.096)	150 (0.101)	40 (1-9/16")	50 (164')	25 (82')
ROUNDIT EMI FMJ 38-8	32 (1-1/4")	38 (1-1/2")	169 (0.113)	176 (0.118)	47 (1-27/32")	35 (115')	25 (82')
ROUNDIT EMI FMJ 50-8	38 (1-1/2")	50 (2")	248 (0.167)	266 (0.179)	65 (2-1/2")	25 (82')	25 (82')
ROUNDIT EMI FMJ 5-8	1 (1/32")	5 (3/16")	30 (0.020)	35 (0.023)	6 (1/4")	250 (820')	100 (328')

Note: Size 5 is designed for cross-talk applications and complies with a maximum R0 at 8 mΩ and a Lt at 1.3 nH. This size is delivered with a white ivory line for maximum operating diameter identification. Lightning strike exposure upon request.

## Part Numbering System

Example	Product Name	Size	Color	Quantity
	ROUNDIT EMI FMJ	8	8 (Light gray)	100 m



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600  
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560  
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565  
[www.systemsprotection.com](http://www.systemsprotection.com)



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

RIEMIFMJ-NA(EN-LTR)B