

ThermoJacket® T



Product Highlights

- Continuous long-term heat protection to +538°C (+1000°F)
- Heavy wall thickness
- High insulation properties



Thermojacket® T is constructed of braided high bulk fiberglass yarn. These yarns provide a heavier wall thickness with only a modest weight increase over other Thermojacket products. Thermojacket T provides excellent insulation properties and withstands continuous heat exposures to +538°C (+1000°F).

Thermojacket sleeving provides excellent long-term heat protection for hoses, wire harnesses and cables. Thermojacket is available in a variety of grades, offering industrial users the option of selecting combination of properties best suited to their specific application.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – ThermoJacket® T

Commercial Part Number	Nominal Size	Approximate Footage Needed to Cover 100 ft
Thermojacket T-8	1/2"	109
Thermojacket T-8	3/4"	116
Thermojacket T-16	1"	109
Thermojacket T-16	1-1/4"	116
Thermojacket T-24	1-1/2"	109
Thermojacket T-30	1-3/4"	116
Thermojacket T-30	2"	116
Thermojacket T-30	2-1/4"	134
Thermojacket T-40	2-1/2"	109
Thermojacket T-40	3"	125

Thermal Protection - Hot Side vs. Cold Side





