



## Product Highlights

- Operating temperature up to +150°C (+302°F)
- High level of abrasion resistance
- Self-wrapping design
- Extremely lightweight and thin
- Used to identify critical components

## Typical Applications

- Electric and hybrid vehicles
- Instrument panel harnesses
- Engine compartment harnesses
- High voltage cables

**TwistTube® 2424LT** is a self-wrapping sleeve designed to provide mechanical protection. Woven of both monofilament and multifilament polyester yarns the product offers a high level of component protection and is both flexible and lightweight. Colored orange, TwistTube 2424LT is commonly used to identify high voltage cables in hybrid vehicles.

The polyester construction eliminates problems associated with trapped heat and humidity and also eliminates operator skin irritation during assembly.

TwistTube 2424LT offers superior abrasion protection and maintains a circular profile when flexed. Its self-wrapping design allows for quick and easy bundling of wire and cable assemblies. The unique design easily allows for breakouts and can be installed over completed assemblies. The lightweight design was developed specifically for electric vehicles and can effectively reduce product weight while still maintaining excellent product performance.



Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

# Performance Data – TwistTube® 2424LT


Property	Test Method	Result
Temperature Rating	240 hrs at +175°C (+150°C rating)	Pass +150°C (+302°F)
Low Temperature Flexibility	SAE J2192	Pass -70°C (-94°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	SAE J2192	Pass

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

## Construction and Typical Product Characteristics

**Warp Yarn:** Polyester (PET) Multifilament

**Fill Yarn:** Polyester (PET) Monofilament



End view of TwistTube 2424LT illustrating self-wrapping construction.

## Standard Sizes

Nominal Diameter mm	Recommended Application Range mm	
	Min Ø	Max Ø
5	3	5
8	5	8
10	9	10
13	11	13
16	14	16
19	17	19
25	20	25
29	26	29
32	30	32

\* Max diameter is defined as a nominal 90 degree sleeve overwrap. A variety of application-based variables will dictate the appropriate sleeve size for use on each harness. Proper sleeve sizing is at the discretion of the end user.

## Availability

Standard sizes are listed here. Additional sizes could be available upon request.

Available in spools and custom cut lengths. Recommended cut lengths are in 5mm increments. Please see regional drawings for cut length tolerances.

Standard color is orange. Additional colors are available.

Please consult your local sales representative for regional packaging details and standards.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600  
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560  
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565  
[www.systemsprotection.com](http://www.systemsprotection.com)



For informational purposes only. SP makes no warranties as to the accuracy or completeness of the information provided herein and disclaims any liability in connection with its use. SP's only obligations are those provided in its terms and conditions of sale for this product, and SP will not be liable for any damages, whether direct or indirect, arising out of the use or misuse of this product. Users should undertake their own evaluations to determine the suitability of the product for specific applications. ©2024 Systems Protection - A Tenneco Company, manufacturer of Bentley-Harris protection products.

TT2424LT-NA(EN-LTR)A