

Product Highlights

- Operating temperature up to +150°C (+302°F)
- Provides electromagnetic shielding
- Self-wrapping design
- Integrated drain wire for proper grounding

Typical Applications

- Instrument panel harnesses
- Engine compartment harnesses
- Battery cables
- Interior harnesses



TwistTube® 2472 is a self-wrapping sleeve designed to provide >30dB of electromagnetic (EM) screening attenuation. 316L fine stainless steel wire is combined with polyester yarn to create a wrappable product that offers flexibility and consistent shielding protection in corrosive environments. The product features an acrylic/silicone coating to prevent end fray and enable cold cutting for specific product lengths.

Unlike foils and films, TwistTube® 2472 is durable and tear resistant, enabling it to provide long term protection. The product is engineered to reduce installation time, accommodate breakouts and can be installed over completed assemblies. An optional 19 AWG, 316L stranded stainless steel wire is integrated into the sleeve for electrical grounding purposes.





Our manufacturing sites are certified ISO 9001, IATF 16949, or AS/EN 9100, ISO 14001 and ISO 45001 (Selected Sites)

Performance Data – TwistTube® 2472

Property	Test Method	Result
Temperature Rating	240 hours at +175°C (+150°F) rating	Pass +150°C (+302°F)
Low Temperature Flexibility	BH100-016A	Pass -70°C (-94°F)
Flammability	SAE J369	Self-extinguishing
Fluid Resistance	BH100-003B	Pass
Salt Spray Endurance	ASTM G85	Pass - no corrosion
Shielding Effectiveness	IEC 62153-4-3	See graph below

All numeric performance data shows average or typical values. Please consult your sales representative for product drawings, test reports and OEM approvals.

Shielding Effectiveness of Slewing



End view of TwistTube 2472 illustrating self-curling wrappable construction with nominal overlap.

Availability

TwistTube 2472 is available in a range of sizes and cut to your specification. Color is black. Please contact your sales representative for availability.



United States: (1) 800 926 2472 • México: (52) 442 101 8100 • Brazil: (55) 19 3116 1600
 EMEA: (33) 3 44 39 06 06 • Japan: (81) 45 330 0300 • China: (86) 21 6182 7560
 Southeast Asia: (66) 35 276 400 • Korea: (82) 44 861 6368 • India: (91) 124 4784565
www.systemsprotection.com

